Head Office:

Monument Office Park 2-101, Steenbok ave, Monument Park PO Box 2354, Brooklyn Square, 0075 Tel: (012) 424 0900 / Fax: (012) 460 1205

Freestate Office:

73 Aliwal Street, Omni Centre, Ground Floor, Office 23, Bloemfontein PO Box 43585, Heuwelsig, 9332, Bloemfontein Tel: (051) 410 5811 / Fax: (086) 692 6981





OUTLINE SERVICES REPORT

JOB No:J005/2013 November 2013

DRAFTED BY HJ BADENHORST

WARDEN TOWNSHIP DEVELOPMENT

Chapter	Desc	Page	
1	INTR	6	
	1.1	Appointment	6
	1.2	Key assumptions	6
	1.3	Scope of the Report	6
2	PRO	7	
	2.1	Project Name	7
	2.2	Locality	7
3	SITE	DESCRIPTION	8
	3.1	Zoning	8
	3.2	Proposed Development	9
	3.3	Topography	9
	3.4	Geology	10
4	AVA	ILABILITY OF BULK SERVICES	13
	4.1	Water	13
	4.2	Sewerage	14
	4.3	Access	15
	4.4	Stormwater	15
5	LEVI	EL OF SERVICE AND DESIGN STANDARDS	16
	5.1	Water Supply	16
	5.2	Sanitation	16
	5.3	Internal Roads	17
	5.4	Stormwater	17
6	PRO	POSED PROJECT PROGRAMME	18
7	CONCLUSIONS AND RECOMMENDATIONS		18

CONTENTS

ANNEXURES

Annexure A	:	LOCALITY PLAN
Annexure B	:	PROPOSED LAYOUT PLAN
Annexure C	:	BULK WATER PROPOSAL
Annexure D	:	BULK SEWER PROPOSAL
Annexure E	:	CONCEPTUAL STORMWATER MANAGEMENT PLAN
Annexure F	:	WATER BOARD MAP OF SOUT AFRICA

1 INTRODUCTION

1.1 Appointment

Badenhorst Konstruksie Trust has been appointed by Pula Strategic Resource Management (Pty) Ltd. to prepare an Outline Services Scheme Report for the proposed new WARDEN Development. The development falls within the jurisdiction of Phumelela Municipality.

1.2 Key assumptions

Pula Strategic Resource Management (Pty) Ltd has been appointed by Phethogo Consulting to undertake basic bulk services planning which includes this development.

This Outline Scheme Report is based on the bulk services information received from Phumelela Municipality

1.3 Scope of the Report

The scope of this report is to identify the availability of bulk services required for the development of and design standards of the internal engineering services.

1.4 Parties Involved

Phumelela Municipality: Mr Johan Oosthuizen (Engineering Services) 073 430 1225

Simlab Geotechnical Services: Mr Barnes J van Vuuren (Geotechnical Investigation) 083 289 3199

Phethogo Consulting (Bloemfontein): Mr P De Bie (Town Planning) 051 448 6006

Consultant: Badenhorst Konstruksie Trust Mr HJ Badenhorst 084 619 5403

2 PROJECT DETAILS

2.1 Project Name

The project is referred to as Ezenzeleni Development and is an integrated mixed use development consisting of approximately 1914 individual residential erven, 8 Business erven, 4 Crèche erven, 9 Religious erven, 11 Public Open erven parks and 1 Multi-purpose erven.

2.2 Locality

The site is located North East of WARDEN, within the Municipal Area of the Phumelela Municipality in the North of the Free State Province.

The site encompasses a total of approximately 113.9 ha, situated approximately 10km north east of the CBD of Warden, and east of the township Ezenzeleni.



The location of the Ezenzeleni Development site is included in Annexure A.

3 SITE DESCRIPTION

3.1 Zoning

3.1.1 Zoning

The site is presently zoned as vacant land and earmarked for Residential Development in the approved SDF. The proposed land uses are contained in section 3.2.

3.1.2 Servitude's

The following servitudes affect the site:

- SANRAL building line next to the N3
- Eskom Power line servitude

3.2 Proposed Development

The proposed site layout is included in Annexure B.

The total site area is approximately 39 hectares and the proposed areas of development are as follows:

ZONING	NUMBER OF STANDS	AREA OF STANDS AND STREETS (ha)	PERCENTAGE %
Residential			
350m ² erven	1 877	23.6780	60.69
General Residential			
Business	8	0.4549	1.17
Institutional			
Schools	4	1.5309	3.92
Crèche	4	0.3605	0.92
Church	9	0.2731	0.70
Public Open Space			
Parks	11	2.7387	7.01
Streets	1	9.9862	25.59
TOTAL	1914	39.0223	`100

3.3 Topography

The proposed township development is situated to the east of the existing township and is underlain by a sandstone and mudstone formation with a positive gradient to the north.

The Cornelis River is just south of the proposed development flowing from east to west.

3.4 Geology

A geotechnical investigation was undertaken by Simlab Geotechnical Services (Bloemfontein) in March 2013. The geology of the site consists of the following:

3.4.1 Regional Geology

The site is underlain by Adelaide Formation of the Beaufort Group (Karoo Super group) consisting mainly of sandstone and mudstone.

The site investigation showed that the site is mainly underlain by sandstone with some mudstone bedrock encountered in some of the test pits.

Aeolian deposits also occur on the site. These refer to silts and sands transported by wind. Aeolian deposits often pertains to collapsible or compressible material.

The area is classified as having a climatic N-value (after Weinert) between 2 and 5, which indicates chemical and mechanical weathering as the main forms of weathering.

3.4.2 Soil Profile

Aeolian – This layer occurs some of the site and consists of loose to medium dense silty sandy material with thickness varying between 0.4m to 0.6m with an average of 0.6m.

Pebble marker – Although not generally encountered, the ferricrete found in some of the test pits may be deemed the pebble marker separating the material deemed to be transported from those considered residual.

Colluvium – Some of the silty sands and sandy silts found on site seems to fit the description of a colluvium material. These are materials that have been transported by water. Colluvium soils situated on straight slopes and planes are usually well drained and exhibit a low collapse potential.

Mudstone – Some mudstone layers have been identified during the investigation, mudstone particles indicate that mudstone bedrock is likely. Depending on the state of the mudrock, it can be a good founding material. Mudstone is susceptible to chemical weathering with mudrock decomposing to form a clayey material.

Alluvial – Some of the clayey materials and silty materials found between 0.6m and 3,0m are considered to be alluvial in nature.

Sandstone – Looking at the bedrock typically encountered during the Geotechnical Investigation, sandstone seems to be the most prevalent. Depending on the state of weathering sandstone can be a good founding material. It may even be used for the construction of road layers and backfilling.

3.4.3 Ground Water and Hydrology

No ground water was encountered during the investigation. Problems due to ground water seepage can be expected in places, especially during and after a very wet rainy season.

3.4.4 Geotechnical Considerations/Recommendations

Refusal at depths between 0.1m than 2.0m was often achieved on material that contained ferricrete, sandstone or mudstone.

The clays on site display varying degrees of expansiveness. The alluvial clays have characteristics of low to medium heaving characteristics. The mudstone is generally less expansive but can sometimes also be highly expansive in a weathered state.

According to the Geotechnical investigation undertaken by Simlab Geotechnical Service, no adverse conditions totally prohibiting the development of the site, depending on the flood level surveys (1:50 year flood-line) (Zone P as classified by the NHBRC Home Building Manual, Part 1 and 2), were observed and the site is zoned into three zones, depending on anticipated total settlement and heave movements as follows:

- **Zone C1** Between 10 and 20mm settlement related (Not mentioned in the report submitted by Simlab Geotechnical Services, but evident in section 8.1 page 11 and Appendix F of the said report).
- Zone H1 Between 7.5mm and 15mm Heave related
- **Zone H2** Between 15mm and 30mm Heave related

NO SITE ZONING PLAN WAS SUBMITTED BY SIMLAB GEOTECHNICAL SERVICES.

The site as a whole, with the exception of the area underlying the 1:50 year floodlevel, is recommended for development. Founding measures that may be considered vary from articulation to concrete raft foundations. Soil mattresses also apply but piling is less likely to be attractive from a single storey housing point of view.

Machine excavation for the installation of services may encounter difficulties due to the fluctuation in the level of very dense material, mudstone bedrock, sandstone bedrock and occasional dolerite bedrock.

The following recommendations are made:

- Special founding solutions must be implemented for all single and double storey structures.
- Detailed geotechnical investigations must be conducted for all high-rise structures, i.e. structures exceeding conventional double storey height.
- Phase 2 investigations must be implemented.
- Because the soils are so variably corrosive, it is recommended that nonferrous materials be used for services piping.

In addition the following drainage measures must be implemented:

- No accumulation of surface water is to be permitted and the entire development must be properly drained.
- All trenches and excavations must be properly backfilled and compacted in 150mm thick layers and compacted to 93% of modified AASHTO density.
- Water borne reticulation must be installed.
- No trees should be planted within five meters of the line of the water bearing services.

4 AVAILABILITY OF BULK SERVICES

4.1 Water

4.1.1 Bulk Services

The bulk water supply to the development will be provided by Phumelela Municipality as a water service provider from the Upper Vaal Regional Network.

It is believed that the existing water infrastructure can support the proposed development of approximately 1914 units in Ezenzeleni due to the newly constructed 5ML reservoir. Ezenzeleni forms a small part of the bigger picture of WARDEN. To support the full development Phumelela Municipality depends on Upper Vaal regional Water for bulk water. The pre-planning of Upper Vaal regional water supply made projections for a prosper growth and water supply was upgraded far beyond the existing needs of WARDEN Municipality. Refer to **Annexure C**.

Written confirmation from Upper Vaal regional water board in support of this is in the process of being obtained.

No Bulk Service contributions will be needed because of the formalizing of the existing in-formalized area. This is part of the bigger picture of the government to rectify the informal housing challenge.

The necessary Augmentation of the Upper Vaal Water network to support the proposed development is the responsibility of Phumelela Municipality and is already in place.

Design criteria:

- UPVC pipes to be used starting from 90mm, 110mm,160mm, 200mm as standard sizes
- No scour and air valves would be needed for WARDEN because it is already covered in the balance of the network.
- A minimum flow of 10 liters/min would be needed.
- Normal clockwise closing valves to be used where no more than four (4) valves need to be closed to isolate an area for maintenance purposes.
- Water meters to be Kent 20mm connections with 15mm meters or similar.
- Pre-paid meters are under consideration.
- The peak factor should be used as 4.
- All fire risks and other criteria according to the specifications set out by the red book (For Human Settlements).

Balance of criteria to the red book standards.

4.2 Sewerage

4.2.1 Bulk Services

Ezenzeleni would be served with water born sewerage with preferably midblock sewers. The following criteria would be needed:

- 1. Materials used should be PVC with the minimum sizes of 160mm
- 2. House connections to be 110 mm.
- 3. Maximum manhole distances of 80 m
- 4. Balance of criteria to the red book standards.

The WARDEN conventional sewer works would be the receiver of the sewerage from Ezenzeleni development. The capacity at WARDEN is lacking at present and the upgrading of this system is undertaken..

At this stage the additional sewer load created by Ezenzeleni development would be substantial and would have a huge impact on the bigger WARDEN capacity. The additional COD load on the works would be small because there are no industrial stands in this development. The WARDEN Sewer Works is hydraulically at design capacity but only \pm 60% organically loaded. This is believed to be as a result of ingress of storm/groundwater, which is supported by the low sewage COD concentrations. Refer to **Annexure D**

Phumelela Municipality has verbally confirmed that drainage of effluent from the above development to the WARDEN Sewer works is acceptable provided that:

- The outfall sewers are re-calculated and augmented as required to accommodate the additional flows. (Little additional COD load is created at the WARDEN sewer works by the development and would be accommodated with the upgrading of WARDEN sewer works.)
- 2. No bulk services contributions would be rendered because of the formalizing the un-formalized housing in this area. No private development is taking place at this stage but is driven by formalizing this area by the municipality.
- 3. It is believed that in the short term, capacity could be increase by reducing the amount of infiltration into the outfall sewer and hence the works.

A tender for the feasibility of the upgrading of WARDEN Wastewater Treatment works for Phumelela Municipality is presently in the pipeline. The scope of this tender includes an evaluation of the WARDEN Wastewater Treatment Works of which a secondary function is the tracing of the sources of infiltration and recommendation of amelioration measures. The planning of the WARDEN sewer works study is expected this year.

4.3 Access

Reference should be made to the Traffic Impact Study prepared by KMA Consulting Engineers that was compiled and completed in October 2013.

The development is situated to the south and east of the existing Ezenzeleni and to the northeast of the main town. The township is situated on both sides of the S807, but mainly on the southern side of the road.

Accesses to the development are from the S807 and are appropriately spaced. Sight distances at these positions are acceptable.

Road reserves are 12m as a minimum, which are acceptable.

4.4 Stormwater

The WARDEN site is located north east of WARDEN CBD, and east of the existing Ezenzeleni.

There are no seasonal streams present on the site. The existing storm water is already captured in the existing open channel grid in this area.

The average rainfall in WARDEN is 680mm and this figure would be used in the final storm water calculations.

Draining in the proposed area would be calculated to a 0.5 - 0.6 run-off factor.

The pipe classes would be class 100 D underneath roads and class 50 - 75 D for other areas according to final designs.

The minimum flow speed should be 1 m/s

The manholes should be distant at 80 m centres maximum.

5 LEVEL OF SERVICE AND DESIGN STANDARDS

5.1 Water Supply

5.1.1 Internal Services

Based on the proposed development outlined in section 3.2 of the report the estimated daily demand of the development is 1.2 MI/day and an estimated peak flow of 56 litres/sec which will have a small impact on the existing delivery.

5.1.2 Proposed Design Standards

Design standards will be as per the Guidelines for Human Settlement Planning and Design and the following design standards are proposed:

• Water consumption:

0	Residential (zone 1)	:	600l/day/erf	
0	Residential (zone 4)	:	600l/day/unit	
0	Business/Municipal	:	400l/day/100m ² of GFA	
0	Primary Schools	:	10Kl/day/ha	
0	Church	:	2000l/day/erf	
0	Crèche	:	10Kl/day/ha	
0	Clinic	:	500l/day/100m ² of GFA	
0	Community Facilities	:	400l/day/100m ² of GFA	
0	Parks	:	12Kl/ha	
Instantaneous Demand Peak Factor: 4				
Pipe m	aterial		uPVC class 12	

• Min residual head during peak flow

5.2 Sanitation

5.2.1 Internal Services

Based on the proposed development outlined in section 3.2 of the report the estimated daily flow from the development is 0.404 Ml/day with an estimated peak flow of 13.4 lt/sec (which includes a 15% infiltration)

24m

A full water borne sanitation system is proposed connecting into the existing bulk/link sewer pipes.

Materials used should be PVC with the minimum sizes of 160mm with house connections to be 110 mm.

Maximum manhole distances of 80 m

Balance of criteria to the red book standards.

5.2.2 Design Standards

Design standards will be as per the Guidelines for Human Settlement Planning and Design and the following design standards are proposed:

•	Sewage Outflow:	200 l/erf/day
٠	Daily Peak Factor:	2.5
٠	Infiltration factor:	15%
٠	Minimum Velocity	0,7m/s
٠	Minimum gradients:	1:120 for 100mm dia.
	1:	200 for 150mm dia.
		1:300 for 200mm dia.
		1:500 for 300mm dia.
•	Maximum manhole spacing:	100 metres
•	Pipe material	uPVC class 34 solid wall
•	Pipe cover	0,6m minimum at head, 1,2m generally
٠	Manholes	Precast concrete rings at 80 meters c/c

5.3 Internal Roads

Design standards will be as per the Guidelines for Human Settlement Planning and Design and the following design standards are proposed:

It is proposed that the internal road network will consist of the following:

- 20m, 16m and 13m road reserve with a 7m, 6m and 5m surfaced width (two lanes per direction) as per layout plan. These road forms the main access through the development and linkage with adjacent development (Higher Order Mixed).
- 16m road reserves, local access routes (Medium Order Mixed).
- 13m road reserves, local access routes (Lower Order Mixed).

Typical cross falls of 3% to be constructed

Typical cross sections are included as Annexure F.

5.4 Stormwater

A conceptual stormwater management plan (SWMP) for the development has been prepared and is included as **Annexure E**.

It is proposed that the WARDEN Development be served by a conventional stormwater drainage system consisting of inlet structures and underground pipes in conjunction with roadways as well as open channels.

The runoff shall be attenuated by means of stormwater detention facilities to be at least equal to pre-development peak flow rates for up to the 1 in 50 year return period storm event.

6 PROPOSED PROJECT PROGRAMME

The main project milestones for this project are as follows

- Township Application to be submitted in NOVEMBER 2013
- Completion of EIA process June 2014

7. CONCLUSIONS AND RECOMMENDATIONS

A bulk water supply sufficient to cater for the initial phases of the development is available directly from existing Upper Vaal Water infrastructure. The Phumelela Local Municipality Water Master Plan supports the full development.

The existing sewage infrastructure is lacking capacity to cater for the initial phases of the development but plans are in place to rectify the need. Sewage from the full development to the WARDEN sewer works is acceptable provided that:

- 1. A need for Outfall sewers upgrading is required to accommodate the additional flows due to existing capacity in main outfall sewers and
- 2. Additional capacity is created at the WARDEN works to accommodate the additional flows.

The development traffic can be accommodated on the existing road network provided that the recommended upgrading requirements are implemented.

Adequate provision has been made within the development layout to provide storm water attenuation to cater for a 50 year flood event.

It is therefore recommended that WARDEN Municipality approve the application for the development of WARDEN

Henry Badenhorst (Pr. Tech (eng) PULA Strategic Resources Management

ANNEXURE A

ANNEXURE B

ANNEXURE C

ANNEXURE D

ANNEXURE E

ANNEXURE F