



ETHEKWINI MUNICIPALITY

Wewe River Floodline at the Proposed Burbreeze Pedestrian Bridge

Final Report

Issue Date: 30 June 2015

Revision No.: 1

Project No.: 12622

Date:	30 June 2015
Document Title:	Wewe River Floodline at the Proposed Burbreeze Pedestrian Bridge
Author:	Lauren Kidgell
Revision Number:	1
Checked by:	Leon Hellberg
Approved:	Leon Hellberg
Signature:	
For:	SiVEST Civil Engineering Division

CONTENTS

1	INTRODUCTION	4
2	METHODOLOGY	5
2.1	HYDROLOGY	5
2.2	HYDRAULICS	6
2.2.1	<i>Wewe River at Dudley Pringle Dam</i>	<i>6</i>
2.2.2	<i>Wewe Stream at Bridge Site.....</i>	<i>6</i>
2.3	EFFECTS OF THE CONSTRUCTED BRIDGE	6
3	RESULTS	7
3.1	HYDROLOGY	7
3.1.1	<i>Dudley Pringle Dam - Standard Design Flood.....</i>	<i>7</i>
3.1.2	<i>Bridge Site– Rational Method.....</i>	<i>8</i>
3.2	HYDRAULICS	8
3.3	EFFECTS OF THE CONSTRUCTED BRIDGE	11
4	DISCUSSION.....	13
5	REFERENCES	14
	APPENDIX A.....	15
	APPENDIX B.....	16
	APPENDIX C.....	17
	APPENDIX D.....	18
	APPENDIX E.....	19

LIST OF FIGURES

Figure 1: Locality map (Google Earth)	4
Figure 2: Catchments areas (Google Earth)	7
Figure 3: Inflow and outflow hydrographs of Dudley Pringle Dam, and combined hydrograph for flow at the bridge site	9
Figure 4: HEC-RAS model geometry of the Burbreeze/ Wewe Stream.....	10
Figure 5: Cross section 5 of the HEC-RAS model during the 100 year flood.	10
Figure 6: Bridge element in the HEC-RAS model	11
Figure 7: Plan view of the bridge element in the HEC-RAS model geometry.....	12

LIST OF TABLES

Table 1: Summary of key hydrological parameters used for the Standard Design Flood.....	8
Table 2: Summary of key hydrological parameters used for the Rational Method.	8
Table 3: Additional Stormwater Runoff associated with Burbreeze Pedestrian Bridge after construction	12

1 INTRODUCTION

SiVEST Civil Engineering Division was appointed by SiVEST Environmental Division to carry out a flood line assessment on the Wewe Stream, in the vicinity of the proposed pedestrian bridge between Sandfields and Burbreeze. Approximate coordinates of the site are:

Latitude 29°32'20.04"S

Longitude 31°08'24.33"E

This investigation aims to achieve the following objectives:

- Study the catchment characteristics of the Wewe River
- Estimate the 100 year flood peak
- Study the river morphology adjacent to the site
- Create a hydrodynamic model of the rivers and impose the 100 year flood scenario.
- Produce a flood line drawing and a succinct report describing the methods utilised.
- Estimate the effects of the bridge on the river and surrounding areas.




Figure 1: Locality map (Google Earth)

2 METHODOLOGY

A floodline study is the result of analyses based on two different scientific procedures. The first procedure involves hydrology, whereby storm flows are estimated from a catchment using statistics to predict the magnitude of various storm events based on historical data. The second procedure relates to hydraulics, which simulates the area under investigation during the flood flow. This involves:

- a) Creating a virtual 3-dimensional frame which simulates the water course in terms of its slope, topography, and roughness,
- b) Introducing the various flood scenarios calculated during the hydrological analysis, and
- c) Recording the results such as water levels and velocities.

2.1 Hydrology

The objective of a hydrological study, in the context of flood line and flood risk assessments, is to estimate the peak flow rate within the river in question for a particular return period. The estimation of peak flow rates are typically achieved by stochastic or deterministic methods.

- Stochastic methods involve analysis of long flow records near the point of interest in the river. There is no flow gauging station on the Wewe River near to the Burbreeze bridge site thus stochastic methods are not applicable to this study.
- Deterministic methods have been developed to estimate floods where reliable statistical data is not available. Simplistically, hypothetical rainfall events are imposed on a catchment area.

Stochastic methods are usually considered superior to deterministic methods, largely because real data records are involved, rather than hypothetical scenarios. Unfortunately stream flow records are seldom long enough (or have not necessarily recorded many extreme events) and are therefore seldom used.

The deterministic method of calculating flood flows for different return periods involved the following steps, as outlined in the SANRAL Drainage Manual, 6th Edition:

- Determine the catchment area of the point of interest on the river.
- Determine the length of the watercourse above the point of interest.
- Calculate the average slope of the river within the catchment (10/85 method)
- Select the appropriate SDF basin number
- Identify the mean annual precipitation of the study area.
- Determine the appropriate design rainfall values to be used, for various return periods

The point of interest along the Wewe Stream is situated downstream of the Dudley Pringle Dam. It is thus necessary to perform hydrological calculations for the catchment of the dam as well as the catchment for the bridge site downstream of the dam.

Of the deterministic methods to be employed, the Standard Design Flood (SDF) is considered to be the most appropriate for Dudley Pringle Dam, due to the large catchment size. The Rational Method is considered to be the most appropriate for the bridge site catchment downstream of the Dudley Pringle dam because this catchment is smaller than 15km².

Results of the calculations are summarised in section 3, while calculation tables are included in Appendix A.

2.2 Hydraulics

2.2.1 Wewe River at Dudley Pringle Dam

Peak flow into the dam is not the same as the discharge over the dam spillway for any given instant. All incoming flows are attenuated in the dam, then water is discharged depending on the water levels in the dam and the spillway characteristics. Inflow is obtained using the SDF method and the outflow will be determined using a depth-storage equation/model in Microsoft Excel for the dam spillway. The following parameters were obtained for this calculation:

- The surface area of the dam at full supply
- The side slopes of the dam
- The design height of the spillway
- The length of the spillway
- The spillway height above the dam bed

The depth-storage spillway calculation data is included in Appendix B.

2.2.2 Wewe Stream at Bridge Site

River morphology was assessed through inspection of highly detailed aerial photography, in order to estimate hydraulic properties such as roughness of the river itself and flood plain areas.

The pedestrian bridge site was surveyed and a 3D terrain model was then produced for use in HEC-RAS, a commonly used software for this type of flood modelling. A series of cross-sections was extracted from the terrain model and input into the hydraulic model to represent the Wewe River. After assigning appropriate roughness and other parameters, the depth of inundation was modelled. HEC-RAS output data is included in Appendix C.

2.3 Effects of the constructed bridge

A bridge element was designed in HEC-RAS according to the bridge design supplied by Ethekewini Municipality Engineering Unit. The HEC-RAS model was re-run incorporating the bridge element at the proposed bridge site. The post-construction output data is also included in Appendix C.

Stormwater runoff from the bridge was estimated to determine what effect it may have on receiving areas.

3 RESULTS

3.1 Hydrology

The catchments of the Dudley Pringle dam and the proposed bridge site downstream of the dam are shown in Figure 2.



Figure 2: Catchments areas (Google Earth)

3.1.1 Dudley Pringle Dam - Standard Design Flood

The catchment area for the Dudley Pringle Dam in particular is considered large, and worthy of a circumspect approach. The Standard Design Flood was developed by Alexander in response to record floods associated with cyclonic activity off the eastern seaboard of Kwazulu-Natal and Mozambique. Alexander's method is considered robust, and the most appropriate deterministic method to be applied for this section of the study. See Table 1 for calculation parameters and results.

Parameter	Wewe River – at the Dudley Pringle Dam
Catchment Area	57.7km ²
Longest Watercourse	17.2km
Average Slope (10/85 method)	0.01475
SDF Basin	24 Newlands
Runoff Coefficient	0.80
Time of Concentration	3.08 hours
Average Intensity	41.28 mm/hour
Q ₁₀₀	529m ³ /s

Table 1: Summary of key hydrological parameters used for the Standard Design Flood.

3.1.2 Bridge Site– Rational Method

Due to the small catchment area of the proposed bridge site downstream of the Dudley Pringle Dam, the Rational Method was used to determine peak flows in the catchment. As identified in the SANRAL Drainage Manual, 6th Edition this method is appropriate for catchments smaller than 15km². See Table 2 for calculation parameters and results.

Parameter	Wewe Stream – at proposed Pedestrian Bridge site
Catchment Area	0.4km ²
Longest Watercourse	0.8km
Average Slope (10/85 method)	0.00482
Runoff Coefficient	0.44
Time of Concentration	0.45 hours
Average Intensity	193.8 mm/hour
Q ₁₀₀	9.3m ³ /s

Table 2: Summary of key hydrological parameters used for the Rational Method.

3.2 Hydraulics

The water levels in the dam were determined using the run-off inflows combined with the dam’s surface area-volume relationship, then the outflows from the dam could be determined by the spillway rating curve. The spillway rating curve for Dudley Pringle Dam was determined using the available properties of the spillway. The rating curve relates the water level in the dam to outflow over the dam spillway. The two equations were executed with a time step of 1 second, from the start of storm rainfall 00:00:00, to the time when spillway flow returned to normal. The Dam spillway model yielded a peak outflow of 423m³/s at 4 hours and 18 minutes after the first rainfall.

See Figure 3 for the combined Hydrograph of the outflow from Dudley Pringle Dam and the Bridge Site catchment downstream of the dam. Due to the small size of the Bridge Site catchment, it had no effect on the maximum flow through the river at the proposed site. 423m³/s is thus the maximum or peak flow for the 100 year flood at the bridge site.




Figure 3: Inflow and outflow hydrographs of Dudley Pringle Dam, and combined hydrograph for flow at the bridge site

Figure 4 shows the geometry set up for the Wewe Stream model in HEC-RAS in which 10 cross sections were taken through the river in the vicinity of the proposed bridge site. Parameters included in the hydraulic model included the following:

- Channel Roughness (Manning's N): 0.04
- Overbank Roughness (Manning's N): 0.06




Figure 4: HEC-RAS model geometry of the Burbreeze/ Wewe Stream

The flow value $423\text{m}^3/\text{s}$ was run through the model in order to determine the 100 year flood line in the vicinity of the proposed bridge site. A typical cross section through the river in flood is presented as Figure 5.




Figure 5: Cross section 5 of the HEC-RAS model during the 100 year flood.

Appendix C contains the output data from the HEC-RAS model. The plan drawing of the 100 year flood line at the bridge site is attached as Appendix D.

3.3 Effects of the constructed bridge

A bridge element was incorporated into the HEC-RAS model in order to model the effects of the proposed bridge once it has been constructed. The bridge element was designed according to the General Arrangement Drawing provided by the Ethekwini Municipality Engineering Unit, attached as Appendix E. The bridge length in the Design Drawing is 36 meters, however the HEC-RAS model output shows that the river width at the proposed bridge site during the 100year flood is estimated to reach approximately 125 meters. The pier spacing is 17.8 meters, which was taken directly from the Ethekwini Design Drawing, and the length of the bridge element between abutments in the HEC-RAS model is 125 meters in order to account for the wider river during flood. Figure 6 shows the model element had 6 piers between abutments as opposed to the Ethekwini Design containing one pier. The bridge deck and pier dimensions were modelled according to the Ethekwini Design.




Figure 6: Bridge element in the HEC-RAS model

The model was then re-run with the bridge element in place between river cross sections 5 and 6, as seen in Figure 7.

The output data of the model including the bridge element is contained in Appendix C. By comparing the data with those of the pre-construction data, one can see that there is approximately a 0.005 m rise in the water surface elevation in the cross sections 9 to 6 upstream of the bridge. Similarly there is an increase in the water velocity in cross sections 9 to 6 of approximately 0.01m/s. There is no change in the data downstream of the bridge element.




Figure 7: Plan view of the bridge element in the HEC-RAS model geometry

It was also necessary to assess the predicted effect on stormwater runoff volumes of the pedestrian bridge after construction. The bridge has a length of 125 meters between abutments. One can be conservative and estimate that an approach ramp of 20 meters on either side of the bridge is to be constructed. This results in an overall concrete length of 165 meters. The bridge width is 2.6 meters. These dimensions yield a hardened surface area of 429m². The table below summarises the additional stormwater runoff associated with the bridge after construction.

Parameter	
Bridge Surface Area	429m ²
Runoff Coefficient (concrete surface)	1
100 year Average Rainfall Intensity (Bridge Site catchment)	193.8 mm/hour
Bridge Runoff	0.0231m ³ /s

Table 3: Additional Stormwater Runoff associated with Burbreeze Pedestrian Bridge after construction

4 DISCUSSION

While every effort has been made to predict, as accurately as possible, the effects of a hypothetical 100 year flood on the river in question, designers should allow for significant error that is the norm in hydrological calculations. This may be done at the discretion of the developer, and may take the form of a freeboard allowance or a buffer zone.

Post-construction of the bridge, the HEC-RAS model revealed that the water surface elevation during a 100 year flood was estimated to increase by 0.05meters which is considered a negligible value. The placement of a Pedestrian Bridge as designed by Ethekwini would thus not impose any significant effect on the flow in the river.

Post-construction stormwater runoff from the bridge would be approximately $0.0231\text{m}^3/\text{s}$. This value can be considered to have a negligible effect on receiving areas.

5 REFERENCES

The South African National Roads Agency Limited (2006) *Drainage Manual, 5th Edition*. Kruger A, Gomes N. The South African National Roads Agency Limited, Pretoria, South Africa

Alexander WJR (1991) *Flood Hydrology for Southern Africa*. Department of Civil Engineering, University of Pretoria.



APPENDIX A

Hydrology

Description of catchment		Standard Design Flood - Dudley Pringle Dam						
River detail		Wewe River						
Calculated by		L. Kidgell			Date		28-04-2015	
Physical characteristics								
Size of catchment (A)	57.68	km ²	Time of Concentration (T _c) $T_c = \left(\frac{0,87 L^2}{1000 S_{av}} \right)^{0,385}$			3.08	hours	
Longest watercourse (L)	17.717	km						
Average slope (S _{av})	0.014750428	m/m	Time of concentration, t (= 60 T _c)			185	minutes	
SDF basin (0) [#]	24		Days of thunder per year (R)			15	days/year	
2-year return period rainfall (M)		76	mm					
TR102 n-day rainfall data								
Weather Service station	Newlands			Mean annual precipitation (MAP)			910	mm
Weather Service station number	240 269			Coordinates		29-59'	&	30-39'
Duration (days)		Return period (years)						
		2	5	10	20	50	100	200
1	76	114	145	181	235	284	340	
2	95	142	181	224	290	348	415	
3	105	154	192	235	298	354	415	
7	126	179	219	262	325	378	436	
Rainfall								
Return period (years), T	2	5	10	20	50	100	200	
Point precipitation depth (mm) P _{T,T}	33.77	56.97	74.52	92.06	115.26	132.81	150.36	
Area reduction factor (%), ARF (= (90000-12800lnA+9830lnT) ^{0,4})	96%	96%	96%	96%	96%	96%	96%	
Average intensity (mm/hour), I _T (= P _{T,T} x ARF / T _c)	10.50	17.71	23.16	28.62	35.83	41.28	46.74	
Run-off coefficients								
Calibration factors	C ₂ (2-year return period) (%)		15	C ₁₀₀ (100-year return period) (%)			80	
Return period (years)	2	5	10	20	50	100	200	
Return period factors (Y _T)	0	0.84	1.28	1.64	2.05	2.33	2.58	
Run-off coefficient (C _T), $C_T = \frac{C_2}{100} + \left(\frac{Y_T}{2,33} \right) \left(\frac{C_{100}}{100} - \frac{C_2}{100} \right)$	0.15	0.38	0.51	0.61	0.72	0.80	0.87	
Peak flow (m ³ /s), Q _T = 0.278 x C _T I _T A	25.23	109.04	188.18	278.55	414.39	529.15	651.29	

Table 3C.7

		2	5	10	20	50	100	200
T _c < 6 hours	Modified Hershfield equation	33.77	56.97	74.52	92.06	115.26	132.81	150.36
6 hours < T _c < 24 hours	Linear interpolation between modified Hershfield equation point rainfall and 1-day point rainfall from TR102	-	-	-	-	-	-	-
T _c > 24 hours	Linear interpolation between n-day point rainfall values from TR103	-	-	-	-	-	-	-


Description of Catchment		Rational Method - Burbreeze Pedestrian Bridge Catchment						
River detail		Wewe Stream						
Calculated by		LK			Date		29-04-2015	
Physical characteristics								
Size of catchment (A)		0.3956		km ²	Rainfall Region			
Longest Watercourse		0.83		km	Area Distribution Factors			
Average slope (S _{av})		0.004819277		m/m	Rural (α)	Urban (β)		Lakes(γ)
Dolomite Area (D%)		0		%	0.5	0.5		0
Mean Annual Rainfall (MAR)		978		mm				
Catchment Characteristics		Flat/permeable		%				
r - look up from Table 3C.3		over fairly rough surface		0.3				
Rural (1)				Urban (2)				
Surface Slope	%	Factor	C _s	Description	%	Factor	C ₂	
Vleis and Pans	0	0.05	-	Lawns				
Flat Areas	40	0.11	0.044	Sandy, flat (<2%)	1	0.075	0.001	
Hilly	55	0.2	0.110	Sandy, steep (>7%)	0	0.175	-	
Steep Areas	5	0.3	0.015	Heavy soil, flat (<2%)	1	0.15	0.002	
Total	100	-	0.169	Heavy soil, steep (>7%)	0	0.3	-	
Permeability	%	Factor	C _p	Residential Areas				
Very Permeable	20	0.05	0.010	Houses	78	0.4	0.312	
Permeable	60	0.1	0.060	Flats	0	0.6	-	
Semi-permeable	20	0.2	0.040	Industry				
Impermeable	0	0.3	-	Light industry	0	0.65	-	
Total	100	-	0.110	Heavy Industry	0	0.75	-	
Vegetation	%	Factor	C _v	Business				
Thick bush and plantation	40	0.05	0.020	City Centre	0	0.825	-	
Light bush and farm-lands	50	0.15	0.075	Suburban	0	0.6	-	
Grasslands	10	0.25	0.025	Streets	20	0.825	0.165	
No Vegetation	0	0.3	-	Maximum flood	0	1.00	-	
Total	100	-	0.120	Total	100	-	0.479	
Time of concentration (T _c)		Defined Watercourse		Notes:				
Overland flow		Defined watercourse						
$T_c = 0.604 \left(\frac{rL}{\sqrt{S_{av}}} \right)^{0.467}$		$T_c = \left(\frac{0.87L^2}{1000S_{av}} \right)^{0.385}$						
1.1 Hours		0.45 Hours						
Run-off coefficient								
Return period (years), T	2	5	10	20	50	100	Max	
Run-off coefficient, C ₁ (C ₁ = C _s + C _p + C _v)	0.399	0.399	0.399	0.399	0.399	0.399	0.399	
Adjusted for dolomitic areas, C _{1D} (= C ₁ (1-D%) + C ₁ D%(Σ(D _{factor} × C _s %)))	0.399	0.399	0.399	0.399	0.399	0.399	0.399	
Adjustment factor for initial saturation, F ₁	0.5	0.55	0.6	0.67	0.83	1	1	
Adjusted run-off coefficient, C _{1T} (= C _{1D} × F ₁)	0.1995	0.21945	0.2394	0.26733	0.33117	0.399	0.399	
Combined run-off coefficient C _T (= αC _{1T} + βC ₂ + γC ₃)	0.339375	0.34935	0.359325	0.37329	0.40521	0.439125	0.439125	
Rainfall								
Return period (years), T	2	5	10	20	50	100	Max	
Point Rainfall (mm), P _T	24.8	37.2	46.9	57.4	73.2	86.8	102.2	
Point Intensity (mm/hour), P _{IT} (=P _T /T _c)	55.3	83.0	104.7	128.1	163.4	193.8	227.9	
Area Reduction Factor (%), ARF _T	99	99	99	99	99	99	99	
Average Intensity (mm/hour), I _T (= P _{IT} × ARF _T)	54.8	82.1	103.6	126.8	161.7	191.8	225.7	
Return period (years), T	2	5	10	20	50	100	Max	
Peak flow (m ³ /s), $Q_T = \frac{C_T I_T A}{3.6}$	2.0	3.2	4.1	5.2	7.2	9.3	10.9	



APPENDIX B

Dam Spillway Data

Spillway parameters			
Item	Unit	Label	Value
Spillway height above dam bed	m	P	3.578
Length of Spillway	m	L	58
Design head of spillway	m	Hd	4
Discharge coefficient	-	Cd	0.483





APPENDIX C

HEC RAS Output Data

HEC-RAS Plan: Pre-construction River: Burbreeze Stream Reach: Burbreeze Stream Profile: Q100

Reach	River Sta	Profile	Q Total (m3/s)	Min Ch El (m)	W.S. Elev (m)	Crit W.S. (m)	E.G. Elev (m)	E.G. Slope (m/m)	Vel Chnl (m/s)	Flow Area (m2)	Top Width (m)	Froude # Chl
Burbreeze Stream	10	Q100	424.00	24.80	29.8020	29.80	31.34	0.009973	7.11	98.41	29.58	1.02
Burbreeze Stream	9	Q100	424.00	24.85	29.3552	28.05	30.40	0.008598	6.23	116.58	39.09	0.94
Burbreeze Stream	8	Q100	424.00	24.75	29.3836		30.14	0.007800	6.04	138.63	54.27	0.90
Burbreeze Stream	7	Q100	424.00	24.58	29.5137		29.92	0.004059	4.49	188.95	73.13	0.65
Burbreeze Stream	6	Q100	424.00	24.40	29.6708		29.81	0.000888	2.25	324.92	99.88	0.31
Burbreeze Stream	5	Q100	424.00	24.05	29.6752		29.78	0.000645	1.98	392.75	132.38	0.27
Burbreeze Stream	4	Q100	424.00	24.80	29.6275		29.76	0.000845	2.06	316.34	94.32	0.30
Burbreeze Stream	3	Q100	424.00	24.56	29.3376		29.71	0.002289	3.30	192.04	60.27	0.49
Burbreeze Stream	2	Q100	424.00	24.08	28.9531		29.63	0.003643	4.16	144.51	47.93	0.62
Burbreeze Stream	1	Q100	424.00	23.99	28.7824	28.37	29.56	0.004001	4.48	147.12	59.41	0.65

HEC-RAS Plan: Post-construct River: Burbreeze Stream Reach: Burbreeze Stream Profile: Q100

Reach	River Sta	Profile	Q Total (m3/s)	Min Ch El (m)	W.S. Elev (m)	Crit W.S. (m)	E.G. Elev (m)	E.G. Slope (m/m)	Vel Chnl (m/s)	Flow Area (m2)	Top Width (m)	Froude # Chl
Burbreeze Stream	10	Q100	424.00	24.80	29.8020	29.80	31.34	0.009973	7.11	98.41	29.58	1.02
Burbreeze Stream	9	Q100	424.00	24.85	29.3594	28.05	30.40	0.008562	6.22	116.74	39.10	0.94
Burbreeze Stream	8	Q100	424.00	24.75	29.3891		30.14	0.007750	6.02	138.93	54.29	0.90
Burbreeze Stream	7	Q100	424.00	24.58	29.5185		29.93	0.004037	4.48	189.31	73.15	0.65
Burbreeze Stream	6	Q100	424.00	24.40	29.6748	27.06	29.81	0.000885	2.24	325.31	99.89	0.31
Burbreeze Stream	5.8	Bridge										
Burbreeze Stream	5	Q100	424.00	24.05	29.6752		29.78	0.000645	1.98	392.75	132.38	0.27
Burbreeze Stream	4	Q100	424.00	24.80	29.6275		29.76	0.000845	2.06	316.34	94.32	0.30
Burbreeze Stream	3	Q100	424.00	24.56	29.3376		29.71	0.002289	3.30	192.04	60.27	0.49
Burbreeze Stream	2	Q100	424.00	24.08	28.9531		29.63	0.003643	4.16	144.51	47.93	0.62
Burbreeze Stream	1	Q100	424.00	23.99	28.7824	28.37	29.56	0.004001	4.48	147.12	59.41	0.65





APPENDIX D

Flood Line Drawing




APPENDIX E


Bridge Design Drawing




PLAN OF CENTRE PIER BASE
1:25




SECTIONAL ELEVATION
CENTRE PIER
1:25



SECTIONAL ELEVATION
NORTH / SOUTH ABUTMENTS
1:25



DETAIL OF SEALING BETWEEN
ABUTMENT AND DECK



LONGITUDINAL ELEVATION
1:50

Contract No 1R - XXXX	
Project Title CONSTRUCTION OF A PROPOSED PEDESTRIAN BRIDGE - BURBREEZE, WARD 02	
Drawing Title GENERAL ARRANGEMENT	
Scale AS SHOWN	Reference
Designed J.V.H.	Date 08-2014
Checked	Drawn P.G.F
Manager: Structures	
Engineer: Roads Provision	
A.M. Peters Head: Engineering	
Drawing XXXXX	Sheet 1 of Sheets



SiVEST Civil Division

4 Pencarrow Crescent
La Lucia Ridge Office Estate
Umhlanga Rocks

Tel +27 31 581 1500
Fax +27 31 566 2371
Email info@sivest.co.za
www.sivest.co.za

Contact Person: Leon Hellberg
Email: leonh@sivest.co.za