## **HIBISCUS BASIN**

PRODUCT CODE 7023

### DESCRIPTION

Vaal Sanitaryware Hibiscus vitreous china wall mounted basin colour White (code: 7023), size 510 x 405mm with one taphole including integrated overflow and chainstay hole bolted to wall with two x 10mm bolts (code: 8448Z0) and including Classic floor mounted pedestal (code: 7150) and sealed with silicone sealant where basin meets wall with Cobra Watertech Ledimo 15mm chrome plated basin mixer with cast fixed outlet, pop-up waste, mounting kit and angle valves (code: LO-295-044), manufactured in accordance with SANS 226:2004 Type 2 (BS 5412)

### INSTALLATION

The basin may be installed by alternative methods: 1.Bolted to the wall using two 10 mm bolts (code 8448Z0).

2. Supported on a Classic floor mounted pedestal (code 7150).

### Option '

Place basin level against wall surface at correct height and mark fixing hole positions. Remove basin and drill holes. Attach bolts to wall, fit basin and secure. NOTE: Do not overtighten.

### Option 2

When installed on Classic pedestal, place basin on pedestal in correct position. Secure basin to the wall, then use silicone sealant or equivalent under pedestal foot and between back of basin and finished wall surface.

## SPECIAL RECOMMENDATION

Always use silicone sealant or equivalent between basin and finished wall surface area for secure and neat installation.

# HIBISCUS CLOSE COUPLED SUITE

PRODUCT CODE 772654 / 772656"

## **DESCRIPTION**

Vaal Sanitaryware "PRODUCT CODE 772654 / 772656" vitreous china "Hibiscus" close coupled 90° outlet open rim front single flush suite complete with lid and fitments (code 772654), or top dual flush suite (code 772656). Front flush suite available in standard colour range.

# RECOMMENDED ACCESSORIES

Jazz thermoset toilet seat (code 8531Z0)

# INSTALLATION

- 1. Place pan into position and mark hole positions. Remove pan and drill holes. Place pan back into position, fix screw to the floor and secure.
- 2. Assemble all cistern fittings with inlet valve on right hand side of cistern. Fit cistern to pan ensuring sealing ring is in the correct position and tighten wing nuts.

NOTE: Do not use putty as sealer.

- 3. Flush the water line.
- 4. Complete all plumbing connections and test flush. Ensure that the correct water level has been set and that the operating overflow tube height conforms to and operates according to local by-laws and SABS specifications.
- 6. Always use silicone sealant or equivalent between the pan and the finished floor and wall surfaces for a secure and neat installation.

NOTE: The warranty will not apply to any product installed with cement

## DURAVIT D-CODE ACRILIC BUILT IN BATH:

Colour White with WonderGliss coating (code:  $700101\ 00001$ ), size  $1800\ x\ 800\ x\ 420$ mm supported on  $38\ x\ 38$ mm timber battens fixed to adjacent walls and bedded in 1:5 cement mortar on a brick bed, three bricks wide for full length of bath with the void between the bath and enclosing wall filled with 1:10 uncompacted cement mix and point all round with abe Dow Corning 785 acetoxy silicone sealant between bath and tiles, all in accordance with manufacturer's recommendations. The bath to be supplied with Cobra Watertech Damara 15mm chrome plated bath mixer, manufactured in accordance with SANS  $226:2009\ Type\ 2\ (BS\ 5412)$ .

## SQUARE SHOWER TRAY:

 $800 \times 800 \times 150$ mm deep insitu shower-tray tiled with mosaic tiles, all in accordance with the manufacturer's recommendations, manufactured in accordance with SANS 226:2009 Type 2 (BS 5412)..

## PRIMADOR WHITE POWDER COATED ALUMINIUM SINGLE PIVOT SHOWER ENCLOSURE:

Size 890 to 920mm x 1800mm high and 1No. 850 to 895 x 1800mm high return panel, glazed with GSA SmartGlass<sup>TM</sup> clear toughened safety glass, complying with SANS 1263 Part 1, 2 or 3 with name of the manufacturer permanently marked on each sheet visible after glazing, in accordance with NBR N schedule 1 and SANS 10137:2002, all fixed complete to walls including pointing all round both sides of frame, all in accordance with the manufacturer's instructions. To be supplied with approved chrome standard large sunflower shower rose (code: C390CP) and taps.

## ROMAN DIETSCHE PYRIT SANITARY ACCESSORIES OR SIMILAR APPROVED:

- stainless steel toilet brush set (code: 705482), overall size 380 x 95 x 130mm, fixed to wall with Dietsche-glue system.
- **stainless steel toilet roll holder** with lid (code: 704982), overall size 140 x 146 x 70mm, fixed to wall with Dietsche-glue system.
- stainless steel liquid soap dispenser (code: 705982), overall size 190 x 51 x 120mm, fixed to wall with Dietsche-glue system.
- **stainless steel tumbler and holder** (code: 703482), overall size 96 x 68 x 105mm, fixed to wall with Dietsche-glue system.
- **stainless steel soap dish and holder** (code: 703782), overall size 55 x 110 x 125mm, fixed to wall with Dietsche-glue system.
- **stainless steel towel ring** (code: 703882), overall size 205 x 160 x 63mm, fixed to wall with Dietsche-glue system.
- stainless steel glass shelf 60 (code: 704282), overall size 50 x 600 x 150mm, fixed to wall with Dietsche-glue system.
- **stainless steel hook** (code: 703182), overall size 50 x 50 x 52mm, fixed to wall with Dietsche-glue system.
- **Hansgrohe or similar approved** Axor Chrome rectangular shaped wall mirror, size 500 x 900mm with frosted border (code: 412110).

NOT!	SPECIFICAT	IONS TO	) BE	CHECK	ED	wr
ARCHIT						
ALL D	ISCREPENO ECT.	CIES TO	BE RE	PORTED	то	Т
REV	ISIONS:					
REV No:		Descripti	ion :			
		Descripti	ion :			

No:	Date :	Description :

	:B. ILORI
Client :	







$\sqsubseteq$					
Pn	oject title	:			
0	R TAI	иво н	HOME	STEA	D

Dwg title :
SANITARY SPECIFICATION AND ACCESSORIES

Building :

Dwg purpose :	WORKING DRAWING			
Checked:	Drawn :	Scale :		
B. Ilori	L. Maliwa			
Rev. no.	Date	Paper size		
0	11 February 2013	A3		
Project no.	BIZ/ORTH/			
Dwg. no.	BIZ/ORTH/5005-W	D		