

DOORS SCHEDULE					
EXTERNAL	D01	DOOR DESCRIPTION	INTERNAL	D02	DOOR DESCRIPTION
	D01	DOOR DESCRIPTION 44mm thick exterior grade nine pane glass door with glazing beads and solid core single fielded panel door and complying with SABS 545 in meranti timber door frame. Oil treated in accordance with specialist's recommendation. FRAMES PARTICULARS Single rebate meranti timber door frame to specialists and complying to the latest SABS standards, complete with lugs and fixtures. Frame profiles to suit wall thickness (115mm, 230mm, 345mm and) as per floor plans DOOR FINISH Oil treated in accordance with specialist's recommendation and latest SABS standards. FRAME FINISH Oil treated in accordance with specialist's recommendation and latest SABS standards. GLAZING PARTICULARS 6mm thick shutter proof glazing and to be in accordance with the latest SABS standards. IRON MONGERY SPECIFICATIONS: All ironmongery to be as per Ironmongery schedule. HINGES: 3No. stainless steel medium duty butt hinges DOOR HANDLING: As per drawing		D02	DOOR DESCRIPTION 40mm thick interior grade flush panel semi-solid core timber single door and complying with SABS 545 in pressed steel frame. All painted in accordance with architects colour schedule. FRAMES PARTICULARS Standard 1.2mm Pre-painted galvanised steel double rebate pressed metal frame complying to SABS 1129 complete with lugs and fixtures. Frame profiles to suit wall thickness (115mm, 230mm and 345mm) as per floor plans DOOR FINISH Prime with wood primer to comply with SABS, type 2. Paint one (1) Universal under coat to comply with SABS 681, grade 1, and finish with two (2) coats alkylate egg-shell paint to comply with SABS 630, type 1. Colour to architect's approval FRAME FINISH Washable enamel paint finish complying with SABS 723 for primer, SABS681 for undercoat and SABS 630 type 2 for finish coat. Colour to architect's approval GLAZING PARTICULARS: 6mm thick shutter proof glazing and to be in accordance with the latest SABS standards. IRON MONGERY SPECIFICATIONS: All ironmongery to be as per Ironmongery schedule. HINGES: 3No. stainless steel medium duty butt hinges DOOR HANDLING: As per drawing
	D03	DOOR DESCRIPTION 44mm thick exterior grade nine pane glass door with glazing beads and solid core single fielded panel door and complying with SABS 545 in meranti timber door frame. Oil treated in accordance with specialist's recommendation. FRAMES PARTICULARS Single rebate meranti timber door frame to specialists and complying to the latest SABS standards, complete with lugs and fixtures. Frame profiles to suit wall thickness (115mm, 230mm, 345mm and) as per floor plans DOOR FINISH Oil treated in accordance with specialist's recommendation and latest SABS standards. FRAME FINISH Oil treated in accordance with specialist's recommendation and latest SABS standards. GLAZING PARTICULARS 6mm thick shutter proof glazing and to be in accordance with the latest SABS standards. IRON MONGERY SPECIFICATIONS: All ironmongery to be as per Ironmongery schedule. HINGES: 3No. stainless steel medium duty butt hinges DOOR HANDLING: As per drawing		D04	DOOR DESCRIPTION 44mm thick exterior heavy duty solid core single fielded panel door and complying with SABS 545 in meranti timber door frame. Oil treated in accordance with specialist's recommendation. FRAMES PARTICULARS Single rebate meranti timber door frame to specialists and complying to the latest SABS standards, complete with lugs and fixtures. Frame profiles to suit wall thickness (115mm, 230mm, 345mm and) as per floor plans DOOR FINISH Oil treated in accordance with specialist's recommendation and latest SABS standards. FRAME FINISH Oil treated in accordance with specialist's recommendation and latest SABS standards. GLAZING PARTICULARS: None IRON MONGERY SPECIFICATIONS: All ironmongery to be as per Ironmongery schedule. HINGES: 3No. stainless steel medium duty butt hinges DOOR HANDLING: As per drawing DOOR DESCRIPTION 44mm thick exterior grade nine pane glass door with glazing beads and solid core single fielded panel door and complying with SABS 545 in meranti timber door frame. Oil treated in accordance with specialist's recommendation. FRAMES PARTICULARS Single rebate meranti timber door frame to specialists and complying to the latest SABS standards, complete with lugs and fixtures. Frame profiles to suit wall thickness (115mm, 230mm, 345mm and) as per floor plans DOOR FINISH Oil treated in accordance with specialist's recommendation and latest SABS standards. FRAME FINISH Oil treated in accordance with specialist's recommendation and latest SABS standards. GLAZING PARTICULARS: None IRON MONGERY SPECIFICATIONS: All ironmongery to be as per Ironmongery schedule. HINGES: 3No. stainless steel medium duty butt hinges DOOR HANDLING: As per drawing
	D05	DOOR DESCRIPTION Purpose 813mm x 2032mm x 44mm thick heavy duty exterior quality single flush timber door with 3mm thick ply on both sides with 2 consolidated edges fitted to comply with SABS 545 interior exterior grade. FRAMES PARTICULARS: Standard 1.2mm in pressed mild steel door frame with profile matching wall, to comply with SABS 1129, complete with lugs and fixtures, to accommodate 813 x 2032 door leaf. FRAME FINISH: Washable enamel paint finish complying with SABS 723 for primer, SABS681 for undercoat and SABS 630 type 2 for finish coat. Colour to architect's approval DOOR FINISH: Prime with wood primer to comply with SABS, type 2. Paint one (1) Universal under coat to comply with SABS 681, grade 1, and finish with two (2) coats alkylate egg-shell paint to comply with SABS 630, type 1. Colour to architect's approval IRONMONGERY: Lockset - 68mm Profile cylinder sash lock, reversible latch lock boxed, polished brass Lever - Pull handle complete with push plate on the opposite side Door stop - polished brass floor mounted. Approved Aluminium engraving sign plate for appropriate rooms HINGES: 3 no. stainless steel medium duty butt hinges.		D06	DOOR DESCRIPTION 44mm thick exterior grade nine pane glass door with glazing beads and solid core single fielded panel door and complying with SABS 545 in meranti timber door frame. Oil treated in accordance with specialist's recommendation. FRAMES PARTICULARS Single rebate meranti timber door frame to specialists and complying to the latest SABS standards, complete with lugs and fixtures. Frame profiles to suit wall thickness (115mm, 230mm, 345mm and) as per floor plans DOOR FINISH Oil treated in accordance with specialist's recommendation and latest SABS standards. FRAME FINISH Oil treated in accordance with specialist's recommendation and latest SABS standards. GLAZING PARTICULARS: 6mm thick shutter proof glazing and to be in accordance with the latest SABS standards. IRON MONGERY SPECIFICATIONS: All ironmongery to be as per Ironmongery schedule. HINGES: 3No. stainless steel medium duty butt hinges DOOR HANDLING: As per drawing
	D07	DOOR DESCRIPTION 44mm thick exterior heavy duty solid core single fielded panel door and complying with SABS 545 in meranti timber door frame. Oil treated in accordance with specialist's recommendation. FRAMES PARTICULARS Single rebate meranti timber door frame to specialists and complying to the latest SABS standards, complete with lugs and fixtures. Frame profiles to suit wall thickness (115mm, 230mm, 345mm and) as per floor plans DOOR FINISH Oil treated in accordance with specialist's recommendation and latest SABS standards. FRAME FINISH Oil treated in accordance with specialist's recommendation and latest SABS standards. GLAZING PARTICULARS: None IRON MONGERY SPECIFICATIONS: All ironmongery to be as per Ironmongery schedule. HINGES: 6No. stainless steel medium duty butt hinges DOOR HANDLING: As per drawing		D08	DOOR DESCRIPTION 44mm thick exterior grade nine pane glass door with glazing beads and solid core single fielded panel door and complying with SABS 545 in meranti timber door frame. Oil treated in accordance with specialist's recommendation. FRAMES PARTICULARS Single rebate meranti timber door frame to specialists and complying to the latest SABS standards, complete with lugs and fixtures. Frame profiles to suit wall thickness (115mm, 230mm, 345mm and) as per floor plans DOOR FINISH Oil treated in accordance with specialist's recommendation and latest SABS standards. FRAME FINISH Oil treated in accordance with specialist's recommendation and latest SABS standards. GLAZING PARTICULARS: 6mm thick shutter proof glazing and to be in accordance with the latest SABS standards. IRON MONGERY SPECIFICATIONS: All ironmongery to be as per Ironmongery schedule. HINGES: 3No. stainless steel medium duty butt hinges DOOR HANDLING: As per drawing
	D09	DOOR DESCRIPTION 44mm thick exterior grade nine pane glass door with glazing beads and solid core single fielded panel door and complying with SABS 545 in meranti timber door frame. Oil treated in accordance with specialist's recommendation. FRAMES PARTICULARS Single rebate meranti timber door frame to specialists and complying to the latest SABS standards, complete with lugs and fixtures. Frame profiles to suit wall thickness (115mm, 230mm and 345mm) as per floor plans DOOR FINISH Prime with wood primer to comply with SABS, type 2. Paint one (1) Universal under coat to comply with SABS 681, grade 1, and finish with two (2) coats alkylate egg-shell paint to comply with SABS 630, type 1. Colour to architect's approval FRAME FINISH Washable enamel paint finish complying with SABS 723 for primer, SABS681 for undercoat and SABS 630 type 2 for finish coat. Colour to architect's approval GLAZING PARTICULARS: None IRON MONGERY SPECIFICATIONS: All ironmongery to be as per Ironmongery schedule. HINGES: 3No. stainless steel medium duty butt hinges DOOR HANDLING: As per drawing		D10	DOOR DESCRIPTION 40mm thick interior grade flush panel semi-solid core timber single door and complying with SABS 545 in pressed steel frame. All painted in accordance with architects colour schedule. FRAMES PARTICULARS Standard 1.2mm Pre-painted galvanised steel double rebate pressed metal frame complying to SABS 1129 complete with lugs and fixtures. Frame profiles to suit wall thickness (115mm, 230mm and 345mm) as per floor plans DOOR FINISH Prime with wood primer to comply with SABS, type 2. Paint one (1) Universal under coat to comply with SABS 681, grade 1, and finish with two (2) coats alkylate egg-shell paint to comply with SABS 630, type 1. Colour to architect's approval FRAME FINISH Washable enamel paint finish complying with SABS 723 for primer, SABS681 for undercoat and SABS 630 type 2 for finish coat. Colour to architect's approval GLAZING PARTICULARS: 6mm thick shutter proof glazing and to be in accordance with the latest SABS standards. IRON MONGERY SPECIFICATIONS: All ironmongery to be as per Ironmongery schedule. HINGES: 3No. stainless steel medium duty butt hinges DOOR HANDLING: As per drawing
	D11	DOOR DESCRIPTION 40mm thick interior grade flush panel semi-solid core timber single door and complying with SABS 545 in pressed steel frame. All painted in accordance with architects colour schedule. FRAMES PARTICULARS Standard 1.2mm Pre-painted galvanised steel double rebate pressed metal frame complying to SABS 1129 complete with lugs and fixtures. Frame profiles to suit wall thickness (115mm, 230mm and 345mm) as per floor plans DOOR FINISH Prime with wood primer to comply with SABS, type 2. Paint one (1) Universal under coat to comply with SABS 681, grade 1, and finish with two (2) coats alkylate egg-shell paint to comply with SABS 630, type 1. Colour to architect's approval FRAME FINISH Washable enamel paint finish complying with SABS 723 for primer, SABS681 for undercoat and SABS 630 type 2 for finish coat. Colour to architect's approval GLAZING PARTICULARS: None IRON MONGERY SPECIFICATIONS: All ironmongery to be as per Ironmongery schedule. HINGES: 3No. stainless steel medium duty butt hinges DOOR HANDLING: As per drawing		D12	DOOR DESCRIPTION 40mm thick interior grade flush panel semi-solid core timber single door and complying with SABS 545 in pressed steel frame. All painted in accordance with architects colour schedule. FRAMES PARTICULARS Standard 1.2mm Pre-painted galvanised steel double rebate pressed metal frame complying to SABS 1129 complete with lugs and fixtures. Frame profiles to suit wall thickness (115mm, 230mm and 345mm) as per floor plans DOOR FINISH Prime with wood primer to comply with SABS, type 2. Paint one (1) Universal under coat to comply with SABS 681, grade 1, and finish with two (2) coats alkylate egg-shell paint to comply with SABS 630, type 1. Colour to architect's approval FRAME FINISH Washable enamel paint finish complying with SABS 723 for primer, SABS681 for undercoat and SABS 630 type 2 for finish coat. Colour to architect's approval GLAZING PARTICULARS: None IRON MONGERY SPECIFICATIONS: All ironmongery to be as per Ironmongery schedule. HINGES: 3No. stainless steel medium duty butt hinges DOOR HANDLING: As per drawing
	D13	TOILET CUBICLE DOORS DOOR DESCRIPTION 40mm thick interior grade flush panel semi-solid core timber single door and complying with SABS 545 in pressed steel frame. All painted in accordance with architects colour schedule. FRAMES PARTICULARS Standard 1.2mm Pre-painted galvanised steel double rebate pressed metal frame complying to SABS 1129 complete with lugs and fixtures. Frame profiles to suit wall thickness (115mm, 230mm and 345mm) as per floor plans DOOR FINISH Prime with wood primer to comply with SABS, type 2. Paint one (1) Universal under coat to comply with SABS 681, grade 1, and finish with two (2) coats alkylate egg-shell paint to comply with SABS 630, type 1. Colour to architect's approval FRAME FINISH Washable enamel paint finish complying with SABS 723 for primer, SABS681 for undercoat and SABS 630 type 2 for finish coat. Colour to architect's approval GLAZING PARTICULARS: None IRON MONGERY SPECIFICATIONS: All ironmongery to be as per Ironmongery schedule. HINGES: 3No. stainless steel medium duty butt hinges DOOR HANDLING: As per drawing		D14	Purpose made aluminium frame louvre balanced internal double door manufactured with 50mm fixed louvers in depth with a 320mm front mounting flange in accordance with the latest edition of BS1474 and according to the minimum requirements of the Association of Architectural Aluminium Manufacturers of South Africa (AAAMSA), completed with 23-gauge galvanized bird screen on the back, completed with 23-gauge galvanized bird screen on the back, to comply with relevant SABS. FRAMES PARTICULARS: Extruded aluminium sections fabricated in accordance with the latest edition of BS1474 and according to the minimum requirements of the Association of Architectural Aluminium Manufacturers of South Africa (AAAMSA). FRAME FINISH: Frame to be finished with powder coating in strict accordance to SABS 1578 all coating quality procedures must be executed and recorded in accordance with SABS ISO 9002. Colour to architect's approval. DOOR FINISH: Prime with wood primer to comply with SABS, type 2. Paint one (1) Universal under coat to comply with SABS 681, grade 1, and finish with two (2) coats alkylate egg-shell paint to comply with SABS 630, type 1. Colour to architect's approval IRONMONGERY: Lockset - Profile cylinder deadlock with adjustable roller bolt latch boxed as supplied by DCLSA (code 69240) Lever - Pull handle as supplied by DCLSA (code 6278/P8) Door stop - polished brass floor mounted as supplied by DCLSA (code 140/71) Approved Aluminium engraving sign plate for appropriate rooms HINGES: 3 no. medium duty butt hinges.
	D15	DOOR DESCRIPTION 40mm thick interior grade flush panel semi-solid core timber single door and complying with SABS 545 in pressed steel frame. All painted in accordance with architects colour schedule. FRAMES PARTICULARS Standard 1.2mm Pre-painted galvanised steel double rebate pressed metal frame complying to SABS 1129 complete with lugs and fixtures. Frame profiles to suit wall thickness (115mm, 230mm and 345mm) as per floor plans DOOR FINISH Prime with wood primer to comply with SABS, type 2. Paint one (1) Universal under coat to comply with SABS 681, grade 1, and finish with two (2) coats alkylate egg-shell paint to comply with SABS 630, type 1. Colour to architect's approval FRAME FINISH Washable enamel paint finish complying with SABS 723 for primer, SABS681 for undercoat and SABS 630 type 2 for finish coat. Colour to architect's approval GLAZING PARTICULARS: None IRON MONGERY SPECIFICATIONS: All ironmongery to be as per Ironmongery schedule. HINGES: 3No. stainless steel medium duty butt hinges DOOR HANDLING: As per drawing		D16	DOOR DESCRIPTION 40mm thick interior grade flush panel semi-solid core timber single door and complying with SABS 545 in pressed steel frame. All painted in accordance with architects colour schedule. FRAMES PARTICULARS Standard 1.2mm Pre-painted galvanised steel double rebate pressed metal frame complying to SABS 1129 complete with lugs and fixtures. Frame profiles to suit wall thickness (115mm, 230mm and 345mm) as per floor plans DOOR FINISH Prime with wood primer to comply with SABS, type 2. Paint one (1) Universal under coat to comply with SABS 681, grade 1, and finish with two (2) coats alkylate egg-shell paint to comply with SABS 630, type 1. Colour to architect's approval FRAME FINISH Washable enamel paint finish complying with SABS 723 for primer, SABS681 for undercoat and SABS 630 type 2 for finish coat. Colour to architect's approval GLAZING PARTICULARS: None IRON MONGERY SPECIFICATIONS: All ironmongery to be as per Ironmongery schedule. HINGES: 3No. stainless steel medium duty butt hinges DOOR HANDLING: As per drawing
	D17	PARALEGIC TOILET DOOR DESCRIPTION 44mm thick interior grade flush solid core timber single door with 3mm thick commercial ply on both sides with consolidated edges fitted and complying with SABS 545 in pressed steel frame. All painted in accordance with architects colour schedule. FRAMES PARTICULARS Standard 1.2mm Pre-painted galvanised steel double rebate pressed metal frame complying to SABS 1129 complete with lugs and fixtures. Frame profiles to suit wall thickness (115mm, 230mm and 345mm) as per floor plans DOOR FINISH Prime with wood primer to comply with SABS, type 2. Paint one (1) Universal under coat to comply with SABS 681, grade 1, and finish with two (2) coats alkylate egg-shell paint to comply with SABS 630, type 1. Colour to architect's approval FRAME FINISH Washable enamel paint finish complying with SABS 723 for primer, SABS681 for undercoat and SABS 630 type 2 for finish coat. Colour to architect's approval GLAZING PARTICULARS: None IRON MONGERY SPECIFICATIONS: All ironmongery to be as per Ironmongery schedule. HINGES: 3No. stainless steel medium duty butt hinges DOOR HANDLING: As per drawing		D18	DOOR DESCRIPTION Insulated Roller Shutter door as "METRO" or equivalent Constructed of galvanized steel flat slats (70 high x 19 deep) with a based on Grey finish on front and back slats. 22 gauge front slat and 24 gauge back slat, enclosing sections of 18mm rigid polyurethane insulation. Slats to be interlocked to form a curtain with alternating steel end locks for slats. FRAMES PARTICULARS: BRACKET PLATES Minimum 4mm thick steel plates to contain sealed self-aligning ball bearings for the suspension of the counterbalance assembly. GUIDES: Constructed of structural steel angles with vinyl snap on weatherstripping. BOTTOM BAR: Extruded aluminium T-shaped member with astragal. HOOD: Constructed of 24 gauge galvanized steel, backed on Grey finish to match curtain and internal hood baffle. DOOR FINISH: Galvanized steel FRAME FINISH: Galvanized steel IRON MONGERY SPECIFICATIONS: SAFETY EDGE Pneumatic or electrical safety edge used to stop or stop/reverse a closing door when it hits an obstruction in the opening. COUNTERBALANCE ASSEMBLY: Consisting of tempered helical torsion springs with 25% safety factor, mounted on shaped cast anchors, supported by continuous solid torsion rod. This mechanism is permanently lubricated and enclosed within a steel pipe shaft. The spring tension adjusting wheel is to be readily accessible from outside the bracket plate. LOCKING: Chain hasp supplied for padlock and cylinder locks on bottom bar. Access control system to be included. MOTOR OPERATION: Integrated electrical components - consisting of a high torque motor, braking system, self-locking gearing, electrical safety interlock, internal pre-wiring, and supplied with a standard push button station. HINGES: None DOOR HANDLING Supply and installation as recommended by manufacturer
	D19	DOOR DESCRIPTION 44mm thick exterior grade nine pane glass door with glazing beads and solid core single fielded panel door and complying with SABS 545 in meranti timber door frame. Oil treated in accordance with specialist's recommendation. FRAMES PARTICULARS Single rebate meranti timber door frame to specialists and complying to the latest SABS standards, complete with lugs and fixtures. Frame profiles to suit wall thickness (115mm, 230mm, 345mm and) as per floor plans DOOR FINISH Oil treated in accordance with specialist's recommendation and latest SABS standards. FRAME FINISH Oil treated in accordance with specialist's recommendation and latest SABS standards. GLAZING PARTICULARS: 6mm thick shutter proof glazing and to be in accordance with the latest SABS standards. IRON MONGERY SPECIFICATIONS: All ironmongery to be as per Ironmongery schedule. HINGES: 3No. stainless steel medium duty butt hinges DOOR HANDLING: As per drawing		D20	DOOR DESCRIPTION 44mm thick exterior heavy duty solid core single fielded panel door and complying with SABS 545 in meranti timber door frame. Oil treated in accordance with specialist's recommendation. FRAMES PARTICULARS Single rebate meranti timber door frame to specialists and complying to the latest SABS standards, complete with lugs and fixtures. Frame profiles to suit wall thickness (115mm, 230mm, 345mm and) as per floor plans DOOR FINISH Oil treated in accordance with specialist's recommendation and latest SABS standards. FRAME FINISH Oil treated in accordance with specialist's recommendation and latest SABS standards. GLAZING PARTICULARS: None IRON MONGERY SPECIFICATIONS: All ironmongery to be as per Ironmongery schedule. HINGES: 6No. stainless steel medium duty butt hinges DOOR HANDLING: As per drawing

NOTES

- ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE STATED
- DIMENSIONS TO BE READ ; NOT TO BE SCALED FROM THIS DRAWING
- CONTRACTORS TO CONFIRM ALL DIMENSIONS ON SITE BEFORE CONSTRUCTION COMMENCES AND ANY DISCREPANCY TO BE REPORTED TO THE PROJECT ARCHITECT

STAGE 03 _DRC SUBMISSION

REV. NO.	DATE	DESCRIPTION
E	15-02-2020	REVISED TO INCORPORATE INPUT FROM THE HERITAGE CONSULTANT COMMENTS OF 28.01.2020 & COORDINATION MEETINGS OF 03.02.2020
D	08-07-2019	REVISION AS PER CLIENT (DOE & DOPW) COMMENTS MADE DURING DOE-SIGON MEETING OF 01.07.2019
C	10-07-2019	REVISION TO INTRODUCE DOOR TYPE D19
B	19-06-2019	REVISION TO INTRODUCE ADDITIONAL DOORS
A	14-08-2016	ORIGINAL FIRST ISSUE

CLIENT DEPARTMENT SIGNATURES		
FACILITY STAMP		
FACILITY MANAGER		
INFRASTRUCTURE MANAGER		
GENERAL MANAGER		
Checked by Professional Consultant Name		
Signature		Date

TECTURA - INTERNATIONAL!

<p>HEAD OFFICE 1001/1002/1003/1004/1005/1006/1007/1008/1009/1010/1011/1012/1013/1014/1015/1016/1017/1018/1019/1020/1021/1022/1023/1024/1025/1026/1027/1028/1029/1030/1031/1032/1033/1034/1035/1036/1037/1038/1039/1040/1041/1042/1043/1044/1045/1046/1047/1048/1049/1050/1051/1052/1053/1054/1055/1056/1057/1058/1059/1060/1061/1062/1063/1064/1065/1066/1067/1068/1069/1070/1071/1072/1073/1074/1075/1076/1077/1078/1079/1080/1081/1082/1083/1084/1085/1086/1087/1088/1089/1090/1091/1092/1093/1094/1095/1096/1097/1098/1099/1100/1101/1102/1103/1104/1105/1106/1107/1108/1109/1110/1111/1112/1113/1114/1115/1116/1117/1118/1119/1120/1121/1122/1123/1124/1125/1126/1127/1128/1129/1130/1131/1132/1133/1134/1135/1136/1137/1138/1139/1140/1141/1142/1143/1144/1145/1146/1147/1148/1149/1150/1151/1152/1153/1154/1155/1156/1157/1158/1159/1160/1161/1162/1163/1164/1165/1166/1167/1168/1169/1170/1171/1172/1173/1174/1175/1176/1177/1178/1179/1180/1181/1182/1183/1184/1185/1186/1187/1188/1189/1190/1191/1192/1193/1194/1195/1196/1197/1198/1199/1200/1201/1202/1203/1204/1205/1206/1207/1208/1209/1210/1211/1212/1213/1214/1215/1216/1217/1218/1219/1220/1221/1222/1223/1224/1225/1226/1227/1228/1229/1230/1231/1232/1233/1234/1235/1236/1237/1238/1239/1240/1241/1242/1243/1244/1245/1246/1247/1248/1249/1250/1251/1252/1253/1254/1255/1256/1257/1258/1259/1260/1261/1262/1263/1264/1265/1266/1267/1268/1269/1270/1271/1272/1273/1274/1275/1276/1277/1278/1279/1280/1281/1282/1283/1284/1285/1286/1287/1288/1289/1290/1291/1292/1293/1294/1295/1296/1297/1298/1299/1300/1301/1302/1303/1304/1305/1306/1307/1308/1309/1310/1311/1312/1313/1314/1315/1316/1317/1318/1319/1320/1321/1322/1323/1324/1325/1326/1327/1328/1329/1330/1331/1332/1333/1334/1335/1336/1337/1338/1339/1340/1341/1342/1343/1344/1345/1346/1347/1348/1349/1350/1351/1352/1353/1354/1355/1356/1357/1358/1359/1360/1361/1362/1363/1364/1365/1366/1367/1368/1369/1370/1371/1372/1373/1374/1375/1376/1377/1378/1379/1380/1381/1382/1383/1384/1385/1386/1387/1388/1389/1390/1391/1392/1393/1394/1395/1396/1397/1398/1399/1400/1401/1402/1403/1404/1405/1406/1407/1408/1409/1410/1411/1412/1413/1414/1415/1416/1417/1418/1419/1420/1421/1422/1423/1424/1425/1426/1427/1428/1429/1430/1431/1432/1433/1434/1435/1436/1437/1438/1439/1440/1441/1442/1443/1444/1445/1446/1447/1448/1449/1450/1451/1452/1453/1454/1455/1456/1457/1458/1459/1460/1461/1462/1463/1464/1465/1466/1467/1468/1469/1470/1471/1472/1473/1474/1475/1476/1477/1478/1479/1480/1481/1482/1483/1484/1485/1486/1487/1488/1489/1490/1491/1492/1493/1494/1495/1496/1497/1498/1499/1500/1501/1502/1503/1504/1505/1506/1507/1508/1509/1510/1511/1512/1513/1514/1515/1516/1517/1518/1519/1520/1521/1522/1523/1524/1525/1526/1527/1528/1529/1530/1531/1532/1533/1534/1535/1536/1537/1538/1539/1540/1541/1542/1543/1544/1545/1546/1547/1548/1549/1550/1551/1552/1553/1554/1555/1556/1557/1558/1559/1560/1561/1562/1563/1564/1565/1566/1567/1568/1569/1570/1571/1572/1573/1574/1575/1576/1577/1578/1579/1580/1581/1582/1583/1584/1585/1586/1587/1588/1589/1590/1591/1592/1593/1594/1595/1596/1597/1598/1599/1600/1601/1602/1603/1604/1605/1606/1607/1608/1609/1610/1611/1612/1613/1614/1615/1616/1617/1618/1619/1620/1621/1622/1623/1624/1625/1626/1627/1628/1629/1630/1631/1632/1633/1634/1635/1636/1637/1638/1639/1640/1641/1642/1643/1644/1645/1646/1647/1648/1649/1650/1651/1652/1653/1654/1655/1656/1657/1658/1659/1660/1661/1662/1663/1664/1665/1666/1667/1668/1669/1670/1671/1672/1673/1674/1675/1676/1677/1678/1679/1680/1681/1682/1683/1684/1685/1686/1687/1688/1689/1690/1691/1692/1693/1694/1695/1696/1697/1698/1699/1700/1701/1702/1703/1704/1705/1706/1707/1708/1709/1710/1711/1712/1713/1714/1715/1716/1717/1718/1719/1720/1721/1722/1723/1724/1725/1726/1727/1728/1729/1730/1731/1732/1733/1734/1735/1736/1737/1738/1739/1740/1741/1742/1743/1744/1745/1746/1747/1748/1749/1750/1751/1752/1753/1754/1755/1756/1757/1758/1759/1760/1761/1762/1763/1764/1765/1766/1767/1768/1769/1770/1771/1772/1773/1774/1775/1776/1777/1778/1779/1780/1781/1782/1783/1784/1785/1786/1787/1788/1789/1790/1791/1792/1793/1794/1795/1796/1797/1798/1799/1800/1801/1802/1803/1804/1805/1806/1807/1808/1809/1810/1811/1812/1813/1814/1815/1816/1817/1818/1819/1820/1821/1822/1823/1824/1825/1826/1827/1828/1829/1830/1831/1832/1833/1834/1835/1836/1837/1838/1839/1840/1841/1842/1843/1844/1845/1846/1847/1848/1849/1850/1851/1852/1853/1854/1855/1856/1857/1858/1859/1860/1861/1862/1863/1864/1865/1866/1867/1868/1869/1870/1871/1872/1873/1874/1875/1876/1877/1878/1879/1880/1881/1882/1883/1884/1885/1886/1887/1888/1889/1890/1891/1892/1893/1894/1895/1896/1897/1898/1899/1900/1901/1902/1903/1904/1905/1906/1907/1908/1909/1910/1911/1912/1913/1914/1915/1916/1917/1918/1919/1920/1921/1922/1923/1924/1925/1926/192</p>
