

R SCI	HED	ULE		
2 280	BD02	DOOR DESCRIPTION 44mm thick exterior grade purpose made fully glazed meranti timber double swing door complying with SABS 545 in meranti timber door frame. Oil treated in accordance with specialist's recommendation. FRAMES PARTICULARS Single rebate meranti timber door frame to specialists and complying to the latest SABS standards, complete with lugs and fixtures. Frame profiles to suit wall thickness (115mm, 230mm, 345mm and) as per floor plans DOOR FINISH Oil treated in accordance with specialist's recommendation and latest SABS standards. FRAME FINISH Oil treated in accordance with specialist's recommendation and latest SABS standards. GLAZING PARTICULARS: 6mm thick shutter proof glazing and to be in accordance with the latest SABS standards. IRON MONGERY SPECIFICATIONS: All ironmongery to be as per Ironmongery schedule. HINGES: 3No. stainless steel medium duty butt hinges DOOR HANDLING : As per drawing	BD03	DOOR DESCRIPTION Purpose made fully glazed meranti timber single swing door with fanlight de SABS 545 in meranti timber door frame. Oil treated in accordance with spe recommendation. FRAMES PARTICULARS Single rebate meranti timber door frame to specialists and complying to the SABS standards, complete with lugs and fixtures. Frame profiles to suit wall thickness (115mm, 230mm, 345mm and) as per DOOR FINISH Oil treated in accordance with specialist's recommendation and latest SAB: FRAME FINISH Oil treated in accordance with specialist's recommendation and latest SAB: GLAZING PARTICULARS: 6mm thick shutter proof glazing and to be in accordance with the latest SAI IRON MONGERY SPECIFICATIONS: All ironmongery to be as per Ironmongery schedule. HINGES: 3No. stainless steel medium duty butt hinges DOOR HANDLING : As per drawing
	BD05	DOOR DESCRIPTION 40mm thick interior grade flush panel semi-solid core timber double door and complying with SABS 545 in pressed steel frame. All painted in accordance with architects colour schedule. FRAMES PARTICULARS Standard 1.2mm mild steel double rebate pressed metal frame complying to SABS 1129 complete with lugs and fixtures. Frame profiles to suit wall thickness (115mm, 230mm and 345mm) as per floor plans DOOR FINISH Prime with wood primer to comply with SABS, type 2. Paint one (1) Universal under coat to comply with SABS 681, grade 1, and finish with two (2) coats alkyde egg-shell paint to comply with SABS 630, type 1. Colour to architect's approval FRAME FINISH Washable enamel paint finish complying with SABS 723 for primer, SABS681 for undercoat and SABS 630 type 2 for finish coat. Colour to architect's approval GLAZING PARTICULARS: none IRON MONGERY SPECIFICATIONS: All ironmongery to be as per Ironmongery schedule. HINGES: 3No. stainless steel medium duty butt hinges DOOR HANDLING : As per drawing DOOR DESCRIPTION		DOOR DESCRIPTION 40mm thick interior grade one panel semi-solid core timber single door and 545 in pressed steel frame. All painted in accordance with architects colour FRAMES PARTICULARS Standard 1.2mm mild steel double rebate pressed metal frame complying to SABS 1129 complete with lugs and fixtures. Frame profiles to suit wall thickness (115mm, 230mm and 345mm) as per fle DOOR FINISH Prime with wood primer to comply with SABS, type 2. Paint one (1) Universe comply with SABS 681, grade 1, and finish with two (2) coats alkyde egg-sh with SABS 630, type 1. Colour to architect's approval FRAME FINISH Washable enamel paint finish complying with SABS 723 for primer, SABS68 SABS 630 type 2 for finish coat. Colour to architect's approval GLAZING PARTICULARS: none IRON MONGERY SPECIFICATIONS: All ironmongery to be as per Ironmongery schedule. HINGES: 3No. stainless steel medium duty butt hinges DOOR HANDLING : As per drawing DOOR DESCRIPTION
		44mm thick exterior grade timber door with nine glass panes with glazing beads and solid core single fielded panel door and complying with SABS 545 in meranti timber door frame. Oil treated in accordance with specialist's recommendation. FRAMES PARTICULARS Single rebate meranti timber door frame to specialists and complying to the latest SABS standards, complete with lugs and fixtures. Frame profiles to suit wall thickness (115mm, 230mm, 345mm and) as per floor plans DOOR FINISH Oil treated in accordance with specialist's recommendation and latest SABS standards. FRAME FINISH Oil treated in accordance with specialist's recommendation and latest SABS standards. GLAZING PARTICULARS: 6mm thick shutter proof glazing and to be in accordance with the latest SABS standards. IRON MONGERY SPECIFICATIONS: All ironmongery to be as per Ironmongery schedule. HINGES: 3No. stainless steel medium duty butt hinges DOOR HANDLING : As per drawing		Existing door: Inspect and make good existing door and complying with SA accordance with architects colour schedule. FRAMES PARTICULARS Existing door frame: Inspect and make good Standard 1.2mm mild steel dou metal frame complying to SABS 1129 complete with lugs and fixtures. DOOR FINISH Prime with wood primer to comply with SABS, type 2. Paint one (1) Universa comply with SABS 681, grade 1, and finish with two (2) coats alkyde egg-sh with SABS 630, type 1. Colour to architect's approval FRAME FINISH Washable enamel paint finish complying with SABS 723 for primer, SABS68 SABS 630 type 2 for finish coat. Colour to architect's approval GLAZING PARTICULARS: none IRON MONGERY SPECIFICATIONS: All ironmongery to be as per Ironmongery schedule. HINGES: Inspect and make good/replace existing: 3No. stainless steel medium duty to DOOR HANDLING : As existing
	BD11	DOOR DESCRIPTION 44mm thick exterior grade timber door with nine glass panes with glazing beads and solid core double fielded panel door and complying with SABS 545 in meranti timber door frame. Oil treated in accordance with specialist's recommendation. FRAMES PARTICULARS Single rebate meranti timber door frame to specialists and complying to the latest SABS standards, complete with lugs and fixtures. Frame profiles to suit wall thickness (115mm, 230mm, 345mm and) as per floor plans DOOR FINISH Oil treated in accordance with specialist's recommendation and latest SABS standards. FRAME FINISH Oil treated in accordance with specialist's recommendation and latest SABS standards. GLAZING PARTICULARS: 6mm thick shutter proof glazing and to be in accordance with the latest SABS standards. IRON MONGERY SPECIFICATIONS: All ironmongery to be as per Ironmongery schedule. HINGES: 3No. stainless steel medium duty butt hinges DOOR HANDLING : As per drawing	BD12	DOOR DESCRIPTION 40mm thick interior grade diagonally slatted semi-solid core timber single do SABS 545 in pressed steel frame. All painted in accordance with architects of FRAMES PARTICULARS Standard 1.2mm mild steel double rebate pressed metal frame complying to SABS 1129 complete with lugs and fixtures. Frame profiles to suit wall thickness (115mm, 230mm and 345mm) as per flo DOOR FINISH Prime with wood primer to comply with SABS, type 2. Paint one (1) Universat comply with SABS 681, grade 1, and finish with two (2) coats alkyde egg-sh with SABS 630, type 1. Colour to architect's approval FRAME FINISH Washable enamel paint finish complying with SABS 723 for primer, SABS68 SABS 630 type 2 for finish coat. Colour to architect's approval GLAZING PARTICULARS: none IRON MONGERY SPECIFICATIONS: All ironmongery to be as per Ironmongery schedule. HINGES: 3No. stainless steel medium duty butt hinges DOOR HANDLING : As per drawing
2040	BD14	DOOR DESCRIPTION 44mm thick interior grade nine pane timber glass door with glazing beads and solid core single fielded panel door with sidelights and complying with SABS 545 in meranti timber door frame. Oil treated in accordance with specialist's recommendation. FRAMES PARTICULARS Single rebate meranti timber door frame to specialists and complying to the latest SABS standards, complete with lugs and fixtures. Frame profiles to suit wall thickness (115mm, 230mm, 345mm and) as per floor plans DOOR FINISH Oil treated in accordance with specialist's recommendation and latest SABS standards. FRAME FINISH Oil treated in accordance with specialist's recommendation and latest SABS standards. GLAZING PARTICULARS: 6mm thick shutter proof glazing and to be in accordance with the latest SABS standards. IRON MONGERY SPECIFICATIONS: All ironmongery to be as per Ironmongery schedule. HINGES: 3No. stainless steel medium duty butt hinges DOOR HANDLING : As per drawing	BD15	DOOR DESCRIPTION TOILET CUBICLE DOORS 40mm thick interior grade flush panel semi-solid core timber single door and 545 in pressed steel frame. All painted in accordance with architects colour FRAMES PARTICULARS Standard 1.2mm Pre-painted galvanised steel double rebate pressed metal SABS 1129 complete with lugs and fixtures. Frame profiles to suit wall thickness (115mm, 230mm and 345mm) as per fle DOOR FINISH Prime with wood primer to comply with SABS, type 2. Paint one (1) Universe comply with SABS 681, grade 1, and finish with two (2) coats alkyde egg-sh with SABS 630, type 1. Colour to architect's approval FRAME FINISH Washable enamel paint finish complying with SABS 723 for primer, SABS68 SABS 630 type 2 for finish coat. Colour to architect's approval GLAZING PARTICULARS: none IRON MONGERY SPECIFICATIONS: All ironmongery to be as per Ironmon HINGES: 3No. stainless steel medium duty butt hinges DOOR HANDLING : As per drawing
	BD17	<ul> <li>DOOR DESCRIPTION: Purpose made fully glazed Aluminium Swing door (Alternatively Perspex or 20mm Vitrex door) in accordance with the latest edition of BS1474 and according to the minimum requirements of AAAMSA.</li> <li>FRAME PARTICULARS: Extruded Aluminium sections fabricated in accordance with the latest edition of BS1474 and according to the minimum requirements of AAAMSA. (Alternatively Perspex or 20mm Vitrex door)</li> <li>DOOR FINISH: Fully glazed Aluminium single swing door according to the minimum requirements of AAAMSA (Alternatively Perspex or 20mm Vitrex door)</li> <li>DOOR FINISH: Fully glazed Aluminium single swing door according to the minimum requirements of AAAMSA (Alternatively Perspex or 20mm Vitrex door). Finished with powder coating to match frames.</li> <li>FRAME FINISH: Frame finished with powder coating in strict accordance to SABS 1578 all coating quality procedures must be executed and recorded in accordance with SABS ISO 9002. Colour to architect's approval.</li> <li>GLAZING PARTICULARS: Glazing shall be executed in strict accordance with the National Building Regulations Part N, SABS 10137, SABS 10400, SABS 1263 and AAAMSA SELECTION GUIDE for SAFETY GLAZING MATERIALS. 8.38mm thick normal strength laminated obscure safety glass.</li> <li>IRON MONGERY SPECIFICATIONS: As per Ironmongery Schedule.</li> <li>HINGES: 3No. medium duty brass hinges at stiles and beds</li> <li>DOOR HANDLING: As per drawing. All Colours to architect's approval.</li> </ul>	ED18	<ul> <li>DOOR DESCRIPTION: Purpose made fully glazed Aluminium Swing door (Alt 20mm Vitrex door) in accordance with the latest edition of BS1474 and accorequirements of AAAMSA.</li> <li>FRAME PARTICULARS: Extruded Aluminium sections fabricated in accordance BS1474 and according to the minimum requirements of AAAMSA. (Alternativ Vitrex door)</li> <li>DOOR FINISH: Fully glazed Aluminium single sliding door according to the mi AAAMSA (Alternatively Perspex or 20mm Vitrex door). Finished with power coating in strict accordance to S procedures must be executed and recorded in accordance with SABS ISO 900 approval.</li> <li>GLAZING PARTICULARS: Glazing shall be executed in strict accordance with Regulations Part N, SABS 10137, SABS 10400, SABS 1263 and AAAMSA SE SAFETY GLAZING MATERIALS. 8.38mm thick normal strength laminated obs IRON MONGERY SPECIFICATIONS: As per Ironmongery Schedule.</li> <li>HINGES: 3No. medium duty brass hinges at stiles and beds</li> <li>DOOR HANDLING: As per drawing. All Colours to architect's approval.</li> </ul>

			NOTES
	oor complying with		
<ul> <li>Multi Writeria</li> <li>Serioration</li> &lt;</ul>			
shows: shows:			
			•CONTRACTORS TO CONFIRM ALL DIMENSIONS ON SITE BEFORE CONSTRUCTION COMMENCES AND ANY
	S standards.		
	BS standards.		
Exception Adds of the second of a seco			_DRC
or y and in and a rank and by and rank and by and a rank and by and rank and by and a ran			208111221011
At set could be the automated       It is abbrowned         At set could be the automated is	)		
et a sit b condy INS 56.44 periodicing INS 56.44 periodi			
BS 55.4 A latical is       E       5-03/372       RE-RECIDITO INCOMPOSATE REMAY THOO THE LOOP OF 30.5000.         Add table present       D       1-02-307       RE-RECIDITO INCOMPOSATE REMAY THOO THE LOOP OF 30.5000.         Add table present       D       1-02-307       RE-RECIDITO INCOMPOSATE REMAY THOO THE LOOP OF 30.5000.         Add table present       D       1-02-307       REMOVED OF ALL-SHORE YOUR SECOND ALL-SHORE YOUR YOUR SECOND ALL-SHORE YOUR SECOND ALL-SHORE YOUR YOUR SECOND ALL-SHORE YOUR YOUR YOUR YOUR SECOND ALL-SHORE YOUR YOUR YOUR YOUR YOUR YOUR YOUR YOUR			
uses 564, 44 pulsed in por relate onesed at refer conting or entate onesed or entate one of enta	31 for undercoat and		
Add in what was and it all not not at all of a not at all not at a not an any hyperbolic structure in the not at all not at a not any hyperbolic structure in the not at all not at a not any hyperbolic structure in the not any hyperbolic structure in thyperbolic structure in the not any hyperbolic structu	ABS 545. All painted in		HERITAGE CONSULTANT COMMENTS OF 28.01.2020 &
bal hanges     b			D 10-07-2019 REVISION AS PER CLIENT (DOE & DOPW) COMMENTS MADE
A is do do do do       Teles:         A is do	uble rebate pressed		C 20-07-2017 REVISION OF FINISHES,(FLOOR PLANS, ELEVATIONS, SECTIONS).
31 Bit undercal and       REV. NO. DATE       DESCRIPTION         bat hinges       REV. NO. DATE       DESCRIPTION         control complying with cobor schedule.       REV. NO. DATE       DESCRIPTION         control complying with cobor schedule.       REV. NO. DATE       DESCRIPTION         control complying with cobor schedule.       Rev. No. DATE       DESCRIPTION         control complying with cobor schedule.       Rev. No. DATE       DESCRIPTION         control complying with cobor schedule.       Rev. No. DATE       DESCRIPTION         control complying with coords to get and control complying with control schedule.       Rev. No. DATE       Description         Signature       Defense       Defense       Rev. No. DATE       Defense         Signature       Defense       Rev. No. Control Consultent       Rev. No. Rev. Rev. Rev. Rev. Rev. Rev. Rev. Rev			TIMBER.
Cluster data data data data data data data dat	81 for undercoat and		
<ul> <li>And complying with object strated, where strated and consolution strated, where strated and consolution strated, where strated and and consolution strated, where strated and and and and and and and and and an</li></ul>	on for undercoat and		
PAOLITY MANAGER      provide cardinal complying with colour acheodies     au under card to     aution c			FACILITY STAMP
bor and correlpting with colour schedule. b or plans al under cost to al and coundy with SABS schedule. 1 for undercoat and pages schedule. 1 for undercoat and gery schedule. 1 for underc	butt hinges		FACILITY MANAGER
be randowned with color achieved. a complete with coords achieved. a lander coat to all pain to comply: all rander coat to all pain to comply: b for undercoat and b complying with SABS achieved. all rander coat to all pain to comply: b and coat to b			
Checked by Professional Consultant advances to see a set of undercoal to a left of underco			
A directional in directional and a directional and directional and a directional and directional directional and directional directi			
#I or undercoat and   If or undercoat and </td <td></td> <td></td> <td></td>			
<text></text>			Signature Date
<ul> <li>d complying with SABS schedule.</li> <li>KEY TO DOOR LEAN</li> <li>Market and the schedule and the interview of the schedule and the sched</li></ul>	81 for undercoat and		GAUTENG NORFOLK HOUSE SANDTON CLOSE TWO
d complying with SABS schedule. Itranstively Perspex or 20mm the latest edition of evely Perspex or 20mm the with the latest edition of evely Perspex or 20mm the latest edition of evely Perspex or			SANDTON         POSTNET SUITE 155         PO.BOX 3158,MAFIKENG 2745         PO.BOX 508           POYATE BAG X9776         TEL(018) 381 8386         KIMBERLY 8300           SANDTON 2146         FAX:+27(0)18 381 8334         TEL:-27(0)53 831 2463           Emailtand@returnal.com         FAX:+27(0)53 831 2475           Tel:+27(0)11783 2084         MPUMALANGA
d complying with SABS schedule. If rame complying to thor pians al under coat to hell paint to compty Bf for undercoat and ngery schedule. Iternatively Perspex or ording to the minimum nee with the latest edition of revip Perspex or Zommi intimum requirements of der coaching to match frames. SABS 1578 all coating quality D2. Colour to architects the National Building ELCTION SQUE for scure safety glass. Iternatively glass. Iternatively Perspex or Zommi intimum requirements of net coating to match frames. SABS 1578 all coating quality D2. Colour to architects Iternatively glass. Iternatively perspex or Zommi intimum requirements of the National Building ELCTION SQUE for scure safety glass. Iternatively glass. Iternatively perspex or Zommi intimum requirements of the National Building ELCTION SQUE for scure safety glass. Iternatively glass. Iternatively perspex or Zommi intimum requirements of the National Building ELCTION SQUE for scure safety glass. Iternatively glass. Iternatively perspex or Zommi intimum requirements of the National Building ELCTION SQUE for scure safety glass. Iternatively perspex or Zommi Iternatively perspex or Zommi Iternativel			Fac: 12 / 013 / 120
LEGEND ON PLAN Iframe complying to loor plans al under coat to hell paint to comply B1 for undercoat and b2 for undercoat b2 for undercoat and b2 for underc			BLOEMFONTEIN, 93015PRIVATE BAG         FAX: +27 (0)36 606 8396         15T FLOOR, LIBERTY BUILDING           FAX: 0866 578094 (ISA ONLY)         12 AURORA DRIVE         12 AURORA DRIVE           Tel: +27 (0)71 692 0404         Email: mpuma@tecturai.com         UMHLANGA 4301           Fax: +27 (0)51 430 5871         TEL: +27 (0)31 535 7132
oor plans         al under coat to         hell pain to comply         31 for undercoat and         agery schedule.         Iternatively Perspex or         rdrig to the minimum         ce with the latest edition of         rely Perspex or 20mm         hinimum requirements of         inder coating to match frames.         ABS 1578 all coating quality         D2 colour to architect's         hte National Building         ELECTION GUIDE for scure safely glass.		LEGEND ON PLAN	ALSO IN NAIROBI, KENYA AND GABORONE, BOTSWANA
al under coat to hell paint to comply B1 for undercoat and Ingery schedule. Iternatively Perspex or rording to the minimum requirements of reder coating to match frames. ABAS 1578 all coating quality 0.2. Colour to architect's the National Building ELECTION GUIDE for scure safety glass. B1 for undercoat and B1 for undercoat and Proposed New Door To Match with Existing Door To Demolish Door Coded Type Existing Door To Demolish Demol	loor plans		Department :
Alt for undercoat and Ingery schedule. Internatively Perspex or proding to the minimum inimum requirements of vider coating to match frames. ABAS 1578 all coating quality 0.2. Colour to architects In the National Building ELECTION GUIDE for scare safety glass. Building the match frames. ABAS 1578 all coating quality D2. Colour to architects In the National Building ELECTION GUIDE for scare safety glass. Building the match frames. ABAS 1578 all coating quality D2. Colour to architects In the National Building ELECTION GUIDE for scare safety glass. Building the match frames. In the National Building ELECTION GUIDE for scare safety glass. Building the match frames. In the National Building ELECTION GUIDE for scare safety glass. Building the match frames. In the National Building ELECTION GUIDE for Scare safety glass. Building the match frames. In the National Building ELECTION GUIDE for Scare safety glass. Building the match frames. In the National Building the Match frames. In the			
Iternatively Perspex or ording to the minimum ce with the latest edition of rely Perspex or 20mm inimum requirements of vder coating to match frames. ABS 1578 all coating quality 02. Colour to architect's the National Building ELECTION GUIDE for scure safety glass. Existing Door To Retain Existing Door To Retain E			Department :
Iternatively Perspex or ording to the minimum       Existing Door To Demolish         inimum requirements of weder coating to match frames.       Existing Door To Demolish         SABS 1578 all coating quality 1002. Colour to architect's       Existing Door To Retain         h the National Building ELECTION GUIDE for uscure safety glass.       Existing Door To Retain	ngery schedule.	Existing Door as Per	REPUBLIC OF SOUTH AFRICA
Iternatively Perspex or ording to the minimum       Existing Door To Demolish       Masterplan Reference: BLOCK B:- DORMITORY         Ince with the latest edition of rely Perspex or 20mm       Dare:       APRIL 2023         Inimum requirements of wder coating to match frames.       Dare:       APRIL 2023         SABS 1578 all coating quality D02. Colour to architect's       Existing Door To Retain       Dare:       APRIL 2023         Masterplan Reference:       BLOCK B:- DORMITORY       Dare:       APRIL 2023         Scale/s       NTS       Consultant Drawing number       E         DOPW Drawing number       120/08       E         DOPW Drawing number       WIMS: 062328       Stamped by Plans Approval Committe			PROVINCE OF KWAZULU-NATAL
brawing description DOOR SCHEDULES Demolish Demolish Demolish Demolish Door SCHEDULES Drawn: BS DATE: APRIL 2023 Scale/s NTS Consultant Drawing number 120/08 E DOPW Drawing number WIMS: 062328 Stamped by Plans Approval Committe			
ce with the latest edition of rely Perspex or 20mm inimum requirements of wder coating to match frames. ABS 1578 all coating quality 02. Colour to architect's h the National Building ELECTION GUIDE for scure safety glass. DATE: APRIL 2023 Scale/s NTS Consultant Drawing number 120/08 E DOPW Drawing number WIMS: 062328		-	
inimum requirements of vder coating to match frames. SABS 1578 all coating quality 102. Colour to architect's th the National Building ELECTION GUIDE for scure safety glass. ELECTION GUIDE for			
ABS 1578 all coating quality 02. Colour to architect's the National Building ELECTION GUIDE for scure safety glass.			Scale/s NTS
The National Building ELECTION GUIDE for scure safety glass.	ABS 1578 all coating quality		120/08 E
scure safety glass.	h the National Building		WIMS: 062328
		BLOCK B	